

The measure  
of all things



## Precision and continuity

---

Ever since its foundation in 1883 Kroeplin have been involved in development and production of handy reliable and precise gauges for the measurement of lengths and thicknesses, especially for the metalworking industry.

Thus the quick test system was created, which was the basis for all further innovations and also for the electronic dial indicators. Experience is the solid foundation for quality.

Careful observation and analysis of the market, flexible realization of requirements, convincing measuring concepts - that is the philosophy that makes Kroeplin successful.

**Today like before, for more than 135 years.**



DIN EN ISO9001:2015

The challenges for the future will be to face market changes, global change as well as ever-shorter development times and to use these challenges to ensure the future of the company.

## Features

---

- Certificate of quality
- Reliable repeatability
- Scales are well arranged and easy to read
- Scale interval from 0.005 mm up
- Numerical interval from 0.001 mm up
- Tolerance marks easy to read
- All mechanical gauges are also available in inch
- The electronic gauges can be switched over to inch
- Measuring contacts are mainly made of carbide
- Electronic gauges with analog/ digital display for better reading
- Mitutoyo interface
- USB interface
- U-WAVE interface
- Bluetooth interface
- Ergonomically designed
- Measuring programs and contacts for different applications
- Absolute and relative measurement
- Red/ Green LED for tolerance measurement (electronic gauges)
- Special solutions possible
- Stand holding unit for serial measurement of small parts
- Convincing price for convincing performance

**Subject to technical alterations.**

## Contents

---

<b>Internal measurement</b>	
Application range up to 60 mm	4–5
Application range up to 120 mm	6–7
Application range exceeding 120 mm	8–9
<b>Internal comparison measurement</b>	10–11
<b>External measurement</b>	
Application range up to 30 mm	12–13
Application range up to 200 mm	14–15
<b>Tube wall measurement</b>	
Application range up to 100 mm	16–17
<b>Measurement of foamed material and foils</b>	
Application range up to 100 mm	18–19
<b>Internal measurement with 3-point contact</b>	20
<b>Accessories   Interfaces</b>	21
<b>Special gauges</b>	22
<b>Definitions</b>	23
<b>Foam inlays</b>	23



Detailed information and data sheets for all gauges are available on our webpage.

[www.kroeplin.com](http://www.kroeplin.com)

# The first electronic quicktest with $\mu\text{m}$ resolution and induction charging technology!

New design and optimized ergonomics.

- Fast reading
- Storage of measuring results
- Precise measuring results
- Quicktest in smallest design
- Numerical interval 0.001 / 0.002 / 0.005 / 0.01 mm
- Lower weight
- Enhanced analog display for optimum reading:
  - 250° analog display range
  - Long analog indicator
- LiPo battery with induction charging technology. Battery change is no longer required!



- Measuring programs for different applications MIN / MAX / HOLD
- Bluetooth interface (up to 8 gauges simultaneously)
- USB, Digimatic and U-Wave® interface
- Compatible to Elias, BOBE, IBR
- 20 % larger data logger (100 measuring values)
- Protection class IP67
- mm / inch switch



Charging station with power supply 8006-20

Can be connected to any device using Bluetooth.



# The established generation of quicktests

electronic



- IP 67
- optimized measuring force
- digital display with analog bar
- ergonomically designed
- Interfaces USB, Digimatic or U-Wave® available on request

mechanical



- IP 65
- optimized measuring force
- accurate measurement
- ergonomically designed

# Internal measurement

Application range up to 60 mm



G002



G102



G210



G330




H105



H210

Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication AzB [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Groove depth A [mm]	Groove width B min [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
G002	10	2.5–12.5	2.4–12.8	0.001	0.010	0.005	0.8	1.3	160	IP67	0.9	0.9	Chisel R 0.12	0.7	0.6	12	[1]	E	1732-38
G005	15	5–20	4.7–20.3	0.001	0.010	0.005	0.8	1.3	160	IP67	2.2	2.2	Ball Ø 0.6	2.2	0.8	44	[2]	E	1732-38
G010	15	10–25	9.7–25.3	0.001	0.010	0.005	0.8	1.3	160	IP67	4.4	4.4	Ball Ø 1	4	1.5	46	[2]	E	1732-38
G102	10	2.5–12.5	2.4–12.8	0.005	0.015	0.005	0.8	1.2	225	IP67	0.9	0.9	Chisel R 0.12	0.7	0.5	12	[1]	E	1732-45
H102	10	2.5–12.5	2.4–12.8	0.005	0.015	0.005	0.8	1.2	155	IP65	0.9	0.9	Chisel R 0.12	0.7	0.5	12	[1]	M	1732-45
G105	10	5–15	4.7–15.3	0.005	0.015	0.005	0.8	1.2	230	IP67	2.5	2.5	Ball Ø 0.6	2.3	0.8	35	[2]	E	1732-45
H105	10	5–15	4.7–15.3	0.005	0.015	0.005	0.8	1.2	160	IP65	2.5	2.5	Ball Ø 0.6	2.3	0.8	35	[2]	M	1732-45
G210	20	10–30	9.5–30.5	0.01	0.03	0.01	1.1	1.6	250	IP67	5.3	5.3	Ball Ø 1	5.2	1.5	85	[2]	E	1732-45
H210	20	10–30	9.5–30.5	0.01	0.03	0.01	1.1	1.6	180	IP65	5.3	5.3	Ball Ø 1	5.2	1.5	85	[2]	M	1732-45
G220	20	20–40	19.5–40.5	0.01	0.03	0.01	1.1	1.6	250	IP67	7.3	7.3	Ball Ø 1	7.0	1.5	85	[4]	E	1732-45
H220	20	20–40	19.5–40.5	0.01	0.03	0.01	1.1	1.6	180	IP65	7.3	7.3	Ball Ø 1	7.0	1.5	85	[4]	M	1732-45
G230	20	30–50	29.5–50.5	0.01	0.03	0.01	1.1	1.6	255	IP67	7.3	7.3	Ball Ø 1	7.0	1.5	85	[4]	E	1732-45
H230	20	30–50	29.5–50.5	0.01	0.03	0.01	1.1	1.6	185	IP65	7.3	7.3	Ball Ø 1	7.0	1.5	85	[4]	M	1732-45
G240	20	40–60	39.5–60.5	0.01	0.03	0.01	1.1	1.6	265	IP67	8.5	8.5	Ball Ø 1	8.3	1.5	85	[5]	E	1732-45
H240	20	40–60	39.5–60.5	0.01	0.03	0.01	1.1	1.6	195	IP65	8.5	8.5	Ball Ø 1	8.3	1.5	85	[5]	M	1732-45
G313	30	13–43	12.5–43.5	0.02	0.04	0.02	1.2	1.7	360	IP67	5.9	5.9	Ball Ø 1.3	5.7	1.6	127	[2]	E	1732-51
G330	30	30–60	29.5–60.5	0.02	0.04	0.02	1.2	1.7	370	IP67	6.5	6.5	Ball Ø 1.5	6.2	1.8	132	[5]	E	1732-51

## Measuring contacts



Chisel R 0.12 mm

Ball Ø 0.6 mm

Ball Ø 1.0 mm

Ball Ø 1.3 mm


Ball Ø 1.0 mm

Ball Ø 1.0 mm

Ball Ø 1.5 mm

Ball Ø 2.0 mm

## Measuring capacity



Meb Measuring range

A Groove depth

B Groove width

Hb Measuring contact movable

Hf Measuring contact fixed

L Measuring depth

# Internal measurement

Application range up to 120 mm



G240



H240



G370



H415




G415



H470

Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Groove depth A [mm]	Groove width B min [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
G250	20	50-70	49.5-70.5	0.01	0.03	0.01	1.1	1.6	265	IP67	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	E	1732-45
H250	20	50-70	49.5-70.5	0.01	0.03	0.01	1.1	1.6	195	IP65	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	M	1732-45
G260	20	60-80	59.5-80.5	0.01	0.03	0.01	1.1	1.6	270	IP67	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	E	1732-45
H260	20	60-80	59.5-80.5	0.01	0.03	0.01	1.1	1.6	200	IP65	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	M	1732-45
G270	20	70-90	69.5-90.5	0.01	0.03	0.01	1.1	1.6	270	IP67	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	E	1732-45
H270	20	70-90	69.5-90.5	0.01	0.03	0.01	1.1	1.6	200	IP65	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	M	1732-45
G280	20	80-100	79.5-100.5	0.01	0.03	0.01	1.1	1.6	270	IP67	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	E	1732-45
H280	20	80-100	79.5-100.5	0.01	0.03	0.01	1.1	1.6	200	IP65	8.5	8.5	Ball Ø 1	8.3	1.2	85	[5]	M	1732-45
G350	30	50-80	49.5-80.5	0.02	0.04	0.02	1.2	1.7	370	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	132	[5]	E	1732-51
G370	30	70-100	69.5-100.5	0.02	0.04	0.02	1.2	1.7	375	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	132	[5]	E	1732-51
G390	30	90-120	89.5-120.5	0.02	0.04	0.02	1.2	1.7	380	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	132	[5]	E	1732-51
G415	50	15-65	14.5-65.5	0.02	0.06	0.04	1.0	1.8	415	IP67	6.0	6.0	Ball Ø 1.5	5.5	1.9	188	[3]	E	1732-51
H415	50	15-65	14.5-65.5	0.05	0.05	0.025	0.9	1.9	355	IP65	6.0	6.0	Ball Ø 1.5	5.5	1.9	188	[3]	M	1732-51
G440	50	40-90	39.5-90.5	0.02	0.06	0.04	1.0	1.8	420	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	E	1732-51
H440	50	40-90	39.5-90.5	0.05	0.05	0.025	0.9	1.9	370	IP65	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	M	1732-51
G470	50	70-120	69.5-120.5	0.02	0.06	0.04	1.0	1.8	420	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	E	1732-51
H470	50	70-120	69.5-120.5	0.05	0.05	0.025	0.9	1.9	370	IP65	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	M	1732-51

## Measuring contacts



Ball Ø 1.0 mm  
Ball Ø 1.5 mm



Ball Ø 1.0 mm  
Ball Ø 2.0 mm

## Measuring capacity



Meb Measuring range      Hb Measuring contact movable  
A Groove depth              Hf Measuring contact fixed  
B Groove width                L Measuring depth

# Internal measurement

Application range exceeding 120 mm



G4100



H4100



G850



H870



G16200



Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication AzB [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Groove depth A [mm]	Groove width B min [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
G4100	50	100–150	99.5–150.5	0.02	0.06	0.04	1.0	1.8	425	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	E	1732-51
H4100	50	100–150	99.5–150.5	0.05	0.05	0.025	0.9	1.9	385	IP65	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	M	1732-51
G4130	50	130–180	129.5–180.5	0.02	0.06	0.04	1.0	1.8	430	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	E	HK
H4130	50	130–180	129.5–180.5	0.05	0.05	0.025	0.9	1.9	390	IP65	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	M	HK
G4150	50	150–200	149.5–200.5	0.02	0.06	0.04	1.0	1.8	435	IP67	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	E	HK
H4150	50	150–200	149.5–200.5	0.05	0.05	0.025	0.9	1.9	395	IP65	8.5	8.5	Ball Ø 2	8.3	2.4	192	[5]	M	HK
G850	100	50–150	49.5–150.5	0.05	0.15	0.1	0.8	2.0	650	IP67	4.0	4.0	Ball Ø 5	3.0	5.5	395	[18]	E	HK
H850	100	50–150	49.5–150.5	0.1	0.15	0.1	0.8	2.0	590	IP65	4.0	4.0	Ball Ø 5	3.0	5.5	395	[18]	M	HK
G870	100	70–170	69.5–170.5	0.05	0.15	0.1	0.8	2.0	650	IP67	14.0	14.0	Ball Ø 5	13.0	5.5	395	[19]	E	HK
H870	100	70–170	69.5–170.5	0.1	0.15	0.1	0.8	2.0	590	IP65	14.0	14.0	Ball Ø 5	13.0	5.5	395	[19]	M	HK
G1290	100	90–190	89–191	0.1	0.3	0.1	1.0	1.5	910	-	13	13	Ball Ø 5	12	5.5	535	[19]	E	HK
H1290	100	90–190	89–191	0.1	0.3	0.1	1.0	1.5	950	-	13	13	Ball Ø 5	12	5.5	535	[19]	M	HK
G12150	100	150–250	149–251	0.1	0.3	0.1	1.0	1.5	920	-	30	30	Ball Ø 5	29	5.5	535	[19]	E	HK
H12150	100	150–250	149–251	0.1	0.3	0.1	1.0	1.5	960	-	30	30	Ball Ø 5	29	5.5	535	[19]	M	HK
G16200	200	200–400	199–401	0.2	0.4	0.2	0.7	1.6	1200	-	29	29	Hemisphere SR 20	28	21	720	[20]	E	HK
H16200	200	200–400	199–401	0.2	0.4	0.2	0.7	1.6	1300	-	29	29	Hemisphere SR 20	28	21	720	[20]	M	HK

## Measuring contacts



Ball Ø 2.0 mm



Ball Ø 5.0 mm




Ball Ø 5.0 mm



Hemisphere SR 20 mm

## Measuring capacity



Meb Measuring range

A Groove depth

B Groove width

Hb Measuring contact movable

Hf Measuring contact fixed

L Measuring depth

# Internal comparison measurement

Application range from 50 to 430 mm



H4M180



H2M50



H2M90



Detailed information and data sheets for all gauges are available on our webpage.

[www.kroepelin.com](http://www.kroepelin.com)


Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Groove depth A [mm]	Groove width B min [mm]	Measuring depth L max. [mm]	Picture	Electronic E	Mechanical M	Wooden box
H2M50	20	50–100	49.5–100.5	0.01	0.03	0.015	1.1	1.6	220	IP65	12.0	variable	Ball Ø 1	8.3	1.2	85	[5]	M		HK
H2M90	20	90–140	89.5–140.5	0.01	0.03	0.015	1.1	1.6	230	IP65	12.0	variable	Ball Ø 1	8.3	1.2	85	[5]	M		HK
H2M130	20	130–180	129.5–180.5	0.01	0.03	0.015	1.1	1.6	240	IP65	12.0	variable	Ball Ø 1	8.3	1.2	85	[5]	M		HK
H4M180	50	180–310	179.5–310.5	0.05	0.10	0.05	0.9	1.9	420	IP65	21.0	variable	Ball Ø 2	8.3	2.2	170	[5]	M		HK
H4M300	50	300–430	299.5–430.5	0.05	0.15	0.05	0.9	1.9	450	IP65	21.0	variable	Ball Ø 2	8.3	2.2	170	[5]	M		HK

## Measuring contact



Ball Ø 1.0 mm  
Ball Ø 2.0 mm

## Measuring capacity



Meb Measuring range  
A Groove depth  
B Groove width  
Hb Measuring contact movable  
Hf Measuring contact fixed  
L Measuring depth

# External measurement

Application range up to 30 mm



C015



POC02K



C220



D220



C330

Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
POCO 2K	10	0-10	0-10	0.1	0.1	0.05	0.3	1.3	40	-	5	5	Ball Ø 2	36	[23]	M	1732-31
POCO 2N	10	0-10	0-10	0.1	0.1	0.05	0.3	1.3	40	-	3.5	3.5	Needle Ø 0.75	36	[24]	M	1732-31
POCO 2F	10	0-10	0-10	0.1	0.1	0.05	0.3	1.3	40	-	4.5	4.5	Sn-R 0.5/F Ø 3.5	36	[25]	M	1732-31
C015	15	0-15	0-15.5	0.001	0.010	0.005	1.3	1.5	170	IP67	17	17	Ball Ø 1.5	45	[6]	E	1732-38
C015S	15	0-15	0-15.5	0.001	0.015	0.005	1.3	1.5	170	IP67	12	12	Chisel R 0.4	45	[7]	E	1732-38
C110	10	0-10	0-10.5	0.005	0.015	0.005	1.2	1.6	240	IP67	19.1	18.6	Ball Ø 1.5	35	[6]	E	1732-45
D110	10	0-10	0-10.5	0.005	0.015	0.005	1.2	1.6	170	IP65	19.1	18.6	Ball Ø 1.5	35	[6]	M	1732-45
C110S	10	0-10	0-10.5	0.005	0.015	0.005	1.2	1.6	240	IP67	18.8	18.5	Chisel R 0.4	35	[7]	E	1732-45
D110S	10	0-10	0-10.5	0.005	0.015	0.005	1.2	1.6	170	IP65	18.8	18.5	Chisel R 0.4	35	[7]	M	1732-45
C220	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	280	IP67	24.7	24.6	Ball Ø 1.5	85	[6]	E	1732-45
D220	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	210	IP65	24.7	24.6	Ball Ø 1.5	85	[6]	M	1732-45
C220S	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	280	IP67	24.7	24.6	Chisel R 0.4	85	[7]	E	1732-45
D220S	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	210	IP65	24.7	24.6	Chisel R 0.4	85	[7]	M	1732-45
C330	30	0-30	0-30.5	0.02	0.04	0.02	0.9	1.6	430	IP67	30	30	Ball Ø 3	116	[6]	E	1732-51
C330S	30	0-30	0-30.5	0.02	0.04	0.02	0.9	1.6	430	IP67	30	30	Chisel R 0.75	116	[7]	E	1732-51

## Measuring contacts



[6] Ball Ø 1.5 mm  
 Ball Ø 3.0 mm


[7] Chisel R 0.4 mm  
 Chisel R 0.75 mm

[23] Ball Ø 2.0 mm

[24] Needle Ø 0.75 mm

[25] Chisel R 0.5 mm  
 Plane Ø 3.5 mm


## Measuring capacity



Meb Measuring range  
 Hb Measuring contact movable  
 Hf Measuring contact fixed  
 L Measuring depth

# External measurement

Application range up to 200 mm




C450



D450



C8100




D450F



C16200


Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force F <sub>min</sub> [N]	Measuring force F <sub>max</sub> [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
C450	50	0-50	0-50.5	0.02	0.06	0.04	0.8	1.7	490	IP67	30	30	Ball Ø 3	167	[6]	E	1732-51
D450	50	0-50	0-50.5	0.05	0.05	0.025	0.8	1.7	430	IP65	30	30	Ball Ø 3	167	[6]	M	1732-51
C450S	50	0-50	0-50.5	0.02	0.06	0.04	0.8	1.7	490	IP67	30	30	Chisel R 0.75	167	[7]	E	1732-51
D450S	50	0-50	0-50.5	0.05	0.05	0.025	0.8	1.7	430	IP65	30	30	Chisel R 0.75	167	[7]	M	1732-51
C450B	50	0-50	0-50.5	0.02	0.08	0.06	0.8	1.7	510	IP67	72.6	30	Ball Ø 5	167	[6]	E	HK
D450B	50	0-50	0-50.5	0.05	0.075	0.05	0.8	1.7	450	IP65	72.6	30	Ball Ø 5	167	[6]	M	HK
C450F	50	0-50	0-50.5	0.02	0.08	0.06	0.8	1.7	510	IP67	30	72.6	Ball Ø 5	167	[6]	E	HK
D450F	50	0-50	0-50.5	0.05	0.075	0.05	0.8	1.7	450	IP65	30	72.6	Ball Ø 5	167	[6]	M	HK
C4100	50	50-100	49.5-100.5	0.02	0.08	0.06	0.8	1.7	510	IP67	30	23	Ball Ø 3	167	[6]	E	HK
D4100	50	50-100	49.5-100.5	0.05	0.075	0.05	0.8	1.7	450	IP65	30	23	Ball Ø 3	167	[6]	M	HK
C4150	50	100-150	99.5-150.5	0.02	0.08	0.06	0.8	1.7	530	IP67	30	23	Ball Ø 3	167	[6]	E	HK
D4150	50	100-150	99.5-150.5	0.05	0.075	0.05	0.8	1.7	470	IP65	30	23	Ball Ø 3	167	[6]	M	HK
C8100	100	0-100	0-101	0.05	0.15	0.1	0.8	1.8	660	IP67	33	33	Ball Ø 5	375	[16]	E	HK
D8100	100	0-100	0-101	0.1	0.15	0.1	0.8	1.8	600	IP65	33	33	Ball Ø 5	375	[16]	M	HK
C12100	100	0-100	0-101	0.1	0.3	0.2	1.2	1.8	950	-	30	30	Ball Ø 5	530	[16]	E	HK
D12100	100	0-100	0-101	0.1	0.3	0.2	1.2	1.8	1000	-	30	30	Ball Ø 5	530	[16]	M	HK
C12100BJ	100	0-100	0-101	0.1	0.3	0.2	1.2	1.8	1100	-	30	124	Ball Ø 5	530	[16]	E	HK
D12100BJ	100	0-100	0-101	0.1	0.3	0.2	1.2	1.8	1100	-	30	124	Ball Ø 5	530	[16]	M	HK
C16200	200	0-200	0-201	0.2	0.4	0.2	0.8	1.5	1300	-	98	98	Hemisphere SR 20	728	[17]	E	HK
D16200	200	0-200	0-201	0.2	0.4	0.2	0.8	1.5	1400	-	98	98	Hemisphere SR 20	728	[17]	M	HK

## Measuring contacts



[6] Ball Ø 2.0 mm  
 [7] Ball Ø 3.0 mm  
 [16] Ball Ø 5.0 mm  
 [17] Hemisphere SR 20 mm

## Measuring capacity



Meb Measuring range  
 Hb Measuring contact movable  
 Hf Measuring contact fixed  
 L Measuring depth

# Tube wall measurement

Application range up to 100 mm



POC02R



C1R10



D2R20



C3R30



D4R50



Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force F <sub>min</sub> [N]	Measuring force F <sub>max</sub> [N]	Weight [g]	Protection class	Type of measuring contact movable [mm]	Measuring contact movable Hb [mm]	Type of measuring contact	Measuring contact fixed Hf [mm]	bore diameter d min	Measuring depth L max [mm]	Picture	Electronic E Mechanical M	Wooden box
POCO 2R	10	0-10	0-10	0.1	0.1	0.05	0.3	1.3	40	-	Ball Ø 2.0	5.0	Hemisphere SR = 0.5	0.8	3	25	[21]	M	1732-31
C0R15	15	0-15	0-15.5	0.001	0.01	0.005	1.3	1.5	165	IP67	Ball Ø 1.5	17	Ball Ø 1.5	0.9	4	46	[8]	E	1732-38
C0R15S	15	0-15	0-15.5	0.001	0.01	0.005	1.3	1.5	170	IP67	Chisel R 0.4	12	Ball Ø 1.5	0.9	4	46	[9]	E	1732-38
C1R10	10	0-10	0-10.5	0.005	0.015	0.005	0.8	1.2	235	IP67	Ball Ø 1.5	19.1	Ball Ø 1.5	0.9	3	35	[8]	E	1732-45
D1R10	10	0-10	0-10.5	0.005	0.015	0.005	0.8	1.2	165	IP65	Ball Ø 1.5	19.1	Ball Ø 1.5	0.9	3	35	[8]	M	1732-45
C1R10S	10	0-10	0-10.5	0.005	0.015	0.005	0.8	1.2	235	IP67	Chisel R = 0.4	18.8	Ball Ø 1.5	0.9	3	35	[9]	E	1732-45
D1R10S	10	0-10	0-10.5	0.005	0.015	0.005	0.8	1.2	165	IP65	Chisel R = 0.4	18.8	Ball Ø 1.5	0.9	3	35	[9]	M	1732-45
C2R20	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	270	IP67	Ball Ø 1.5	24.7	Ball Ø 1.5	2.5	9	80	[10]	E	1732-45
D2R20	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	200	IP65	Ball Ø 1.5	24.7	Ball Ø 1.5	2.5	9	80	[10]	M	1732-45
C2R20S	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	270	IP67	Chisel R = 0.4	24.7	Ball Ø 1.5	2.5	9	80	[11]	E	1732-45
D2R20S	20	0-20	0-20.5	0.01	0.03	0.01	1.1	1.6	200	IP65	Chisel R = 0.4	24.7	Ball Ø 1.5	2.5	9	80	[11]	M	1732-45
C3R30	30	0-30	0-30.5	0.02	0.04	0.02	0.9	1.6	410	IP67	Ball Ø 3	30	Ball Ø 3	4	10	116	[10]	E	1732-51
C3R30S	30	0-30	0-30.5	0.02	0.04	0.02	0.9	1.6	410	IP65	Chisel R = 0.75	30	Ball Ø 3	4	10	116	[11]	E	1732-51
C4R50	50	0-50	0-50.5	0.02	0.06	0.04	0.8	1.7	460	IP67	Ball Ø 3	30	Ball Ø 3	4.3	13	169	[10]	E	1732-51
D4R50	50	0-50	0-50.5	0.05	0.05	0.025	0.8	1.7	400	IP65	Ball Ø 3	30	Ball Ø 3	4.3	13	169	[10]	M	1732-51
C4R50S	50	0-50	0-50.5	0.02	0.06	0.04	0.8	1.7	460	IP67	Chisel R = 0.75	30	Ball Ø 3	4.3	13	169	[11]	E	1732-51
D4R50S	50	0-50	0-50.5	0.05	0.05	0.025	0.8	1.7	400	IP65	Chisel R = 0.75	30	Ball Ø 3	4.3	13	169	[11]	M	1732-51
C8R100	100	0-100	0-101	0.05	0.15	0.1	0.8	1.8	660	IP67	Ball Ø 5	35	Ball Ø 5	15	36	382	[15]	E	HK
D8R100	100	0-100	0-101	0.1	0.15	0.1	0.8	1.8	600	IP65	Ball Ø 5	35	Ball Ø 5	15	36	382	[15]	M	HK

## Measuring contacts

## Measuring capacity



Ball Ø 1.5 mm



Chisel R 0.4 mm  
Ball Ø 1.5 mm



Ball Ø 1.5 mm  
Ball Ø 2.0 mm  
Ball Ø 3.0 mm




Chisel R 0.4 mm  
Chisel R 0.75 mm  
Ball Ø 1.5 mm  
Ball Ø 2.0 mm  
Ball Ø 3.0 mm



Ball Ø 5.0 mm



Ball Ø 2.0 mm  
Hemisphere SR 0.5 mm



Meb Measuring range

Hb Measuring contact movable

Hf Measuring contact fixed

L Measuring depth

d Diameter

# Measurement of foamed material and foils

Application range up to 100 mm




POC02T




C110T



D220T




C330T



D450T

Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication AzB [mm]	Numerical interval Zw Scale interval Skw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
POCO 2T	10	0-10	0-10	0.1	0.1	0.05	0.3	1.3	40	-	5.0	5.0	Flat Ø 10	36	[22]	M	1732-31
C110T	10	0-10	0-10.5	0.005	0.02	0.005	0.8	1.2	175	IP67	21.7	14.8	Flat Ø 6	35	[12]	E	1732-45
D110T	10	0-10	0-10.5	0.005	0.02	0.005	0.8	1.2	175	IP65	21.7	14.8	Flat Ø 6	35	[12]	M	1732-45
C220T	20	0-20	0-20.5	0.01	0.04	0.01	1.1	1.6	220	IP67	28.2	20.7	Flat Ø 10	85	[12]	E	1732-45
D220T	20	0-20	0-20.5	0.01	0.04	0.01	1.1	1.6	220	IP65	28.2	20.7	Flat Ø 10	85	[12]	M	1732-45
C330T	30	0-30	0-30.5	0.02	0.06	0.04	0.9	1.6	430	IP67	36	24	Flat Ø 50	116	[14]	E	1732-51
C450T	50	0-50	0-50.5	0.02	0.08	0.06	0.8	1.7	500	IP67	36	24	Flat Ø 50	167	[14]	E	1732-51
D450T	50	0-50	0-50.5	0.05	0.1	0.05	0.8	1.7	440	IP65	36	24	Flat Ø 50	167	[14]	M	1732-51
C8100T	100	0-100	0-101	0.05	0.15	0.1	0.8	1.8	670	IP67	39	7	Flat Ø 50	375	[14]	E	HK
D8100T	100	0-100	0-101	0.1	0.15	0.1	0.8	1.8	610	IP65	39	7	Flat Ø 50	375	[14]	M	HK
C12100T	100	0-100	0-101	0.1	0.3	0.2	1.6	2.2	1000	-	34	14	Flat Ø 50	550	[14]	E	HK
D12100T	100	0-100	0-101	0.1	0.3	0.2	1.6	2.2	1100	-	34	14	Flat Ø 50	550	[14]	M	HK

## Measuring contacts




Flat Ø 6 mm  
Flat Ø 10 mm

Flat Ø 50 mm

Flat Ø 10 mm

## Measuring capacity



Meb Measuring range  
Hb Measuring contact movable  
Hf Measuring contact fixed  
L Measuring depth

# Internal measurement with 3-point contact

Application range from 7 to 105 mm



G210P3

Type	Measuring span Mes [mm]	Measuring range Meb [mm]	Range of indication Azb [mm]	Numerical interval Zw [mm]	Permissible errors G [mm]	Repeatability limit r [mm]	Measuring force $F_{min}$ [N]	Measuring force $F_{max}$ [N]	Weight [g]	Protection class	Measuring contact movable Hb [mm]	Measuring contact fixed Hf [mm]	Type of measuring contact [mm]	Groove depth A [mm]	Groove width B min [mm]	Measuring depth L max. [mm]	Picture	Electronic E Mechanical M	Wooden box
G107P3	7	7-14	6.8-14.5	0.002	0.01	0.004	1.0	1.4	230	IP67	2.5	-	Ball Ø 0.6	2.2	0.8	34	[1]	E	1732-45
G210P3	10	10-20	9.8-20.5	0.005	0.02	0.01	1.1	1.6	250	IP67	4.6	-	Ball Ø 1	3.5	1.6	75	[2]	E	1732-45
G215P3	15	15-30	14.5-30.5	0.005	0.02	0.01	1.1	1.6	275	IP67	5.8	-	Ball Ø 1	5.0	1.6	77	[2]	E	1732-45
G225P3	20	25-45	24.5-45.5	0.005	0.02	0.01	1.1	1.6	255	IP67	7.3	-	Ball Ø 1	7.0	1.6	84	[3]	E	1732-45
G240P3	20	40-60	39.5-60.5	0.005	0.02	0.01	1.1	1.6	270	IP67	12.2	-	Ball Ø 1	8.0	1.6	84	[3]	E	1732-45
G255P3	20	55-75	54.5-75.5	0.005	0.02	0.01	1.1	1.6	270	IP67	12.2	-	Ball Ø 1	8.0	1.6	84	[3]	E	1732-45
G270P3	20	70-90	69.5-91	0.005	0.02	0.01	1.1	1.6	275	IP67	12.2	-	Ball Ø 1	8.5	1.6	84	[3]	E	1732-45
G285P3	20	85-105	84.5-106	0.005	0.02	0.01	1.1	1.6	285	IP67	12.2	-	Ball Ø 1	9.0	1.6	84	[3]	E	1732-45

## Measuring contacts




Ball Ø 0.6 mm

Ball Ø 1.0 mm

Ball Ø 1.0 mm

## Measuring capacity



Meb Measuring range

A Groove depth

B Groove width

Hb Measuring contact movable

Hf Measuring contact fixed

L Measuring depth

# Interfaces

CO/G0 gauges

Interface adapter  
8006-17



Data cable USB - V2.0

2482-05 ~2 m



Data cable DIGIMATIC - V2.0

2482-07 ~2 m



Data cable U-WAVE® - V2.0

2482-04 ~160 mm



C1/C2/C3/C4/C8 gauges  
G1/G2/G3/G4/G8 gauges



Interface adapter  
1961-09

CO/G0 gauges



Interface adapter  
Bluetooth  
8006-16

Also in combination with  
smartphone and tablet!

USB-Bluetooth-V4.0-  
dongle included!  
0682-60



Interfaces may be upgraded on demand.


Simultaneous connection of up to 8 gauges possible.

# Accessories

- Wooden boxes for all series
- For order code please see technical details (HK = wooden box is included in delivery)



For measuring small parts the holding unit enables the gauge (series C, G, D, H) to be used with a measuring stand.



Gauge G102  
(available on request)

Holder CO/G0	order no.: 8004-58
Holder C1/G1/D1/H1/C2/G2/D2/H2	order no.: 8004-50
Holder C3/G3/D4/C4/H4/G4	order no.: 8004-55


## Special gauges

**We are always searching for the best solution for your measuring problem, either mechanical or electronic.**

In order to enable us to find the solution together and to design your special gauge, please kindly send us a drawing of the object to be measured and indicate tolerance and measuring force, and if possible, send us a sample of the part to be measured. Full information in your enquiry enables us to put forward the optimum design solution for your application.

The gauges shown are examples of special applications. For additional measuring applications we offer customised solutions.

► Measurements of undercuts with inclined measuring contacts.




► Measurements of wall thicknesses in hard-to-access places.




► Measurements in hard-to-access places with specially designed caliper arms.




► Measurement of bottle diameters with depth measurement.



► Measurements of foamed materials with flat contacts and reduced measuring force.



► Measurements of wall thicknesses at large undercuts with bayonet-type contacts (displacement in direction of the arrow before and after the measurement).



Detailed information and data sheets for all gauges are available on our webpage.

[www.kroepin.com](http://www.kroepin.com)

# Foam inlays for storing measuring instruments

As an optional accessory we offer customised foam inlays for storing instruments e.g. in drawer cabinets.


Let us know the external dimensions as well as the number and type of Kroeplin gauges to be accommodated. If you would like to integrate different manufacturers' products or tools together with Kroeplin gauges in one inlay, we can implement this based on your 2D CAD data.

Based on your data we will send an appropriate offer. Please contact us.



## Definitions

### Diagram of deviation



The individual diagram of deviation you can see in the certificate of quality which will be sent with every gauge.

### Definitions

Terms of length test techniques see DIN 2257 part 1 and part 2 and International Vocabulary of Basic and General Terms in Metrology.

### Foundations

This instruction follows approximately the checking instructions of the German standard DIN 878 for dial gauges and the checking instructions for caliper gauges according to VDI/VDE/DGQ 2618, page 13. The gauges are referred to as gauges with absolute measurement and adjustable zero point.

### Measuring span Mes

The measuring span is the difference between starting value and final value of the measuring range.

### Measuring range Meb

The measuring range of a gauge represents the range of measuring values in which given error limits must not be exceeded.

### Range of indication Azb

The range of indication is the range between the highest and the lowest indication.

### Numerical interval Zw

The numerical interval is the difference between two consecutive numbers of the last digit shown in the display. The numerical interval of a numerical scale is the modification of the value of a measured variable that causes the modification of the indication by one interval. The numerical interval corresponds to the scale interval of a line scale and is indicated in the unity of the measured variable.

### Scale interval Skw

The scale interval is the modification of the value of a measured variable that causes the modification of the indication by one interval. The scale interval is indicated in the unity of the measured variable.

### Deviation in the measuring range $f_M$

The deviation in the measuring range  $f_M$  represents the distance of ordinates between the highest and the lowest position in the deviation diagram, when the movable caliper arm closes. The **tolerance field G** for  $f_M$  is symmetrically positioned to the zero line.

### Repeat precision $f_w$

The repeat precision  $f_w$  is a characteristic value for deviations of the measured quantity within the measuring range when the movable caliper arm closes (usually  $n=5$ ). This margin of error is designated as **repeat limit r**.

### Measuring force $F_{min}$ , $F_{max}$

When the caliper arm closes, the measuring force  $F_{min}$  or  $F_{max}$  is determined at the top of the movable caliper arm. The gauge must be held in vertical position  $\geq 200$  mm.



## Application area

- Mechanical engineering
- Automobile industry
- Aerospace industry
- Wire manufacturers
- Glass industry
- Dental laboratories
- Aerosol and packaging industry
- Foundries
- Foamed material industry
- Tube manufacturers
- Ceramic industry
- Medical institutes
- Special designs

Kroeplin GmbH  
Gartenstraße 50 | 36381 Schluechtern | Germany

Phone: +49 (0)6661 86-0  
Fax: +49 (0)6661 86-39

e-mail: [sales@kroeplin.com](mailto:sales@kroeplin.com)  
[www.kroeplin.com](http://www.kroeplin.com)

In the centre  
of Europe.



The measure of all things.

Kroeplin Längenmesstechnik: Innovative and precise measuring instruments for exact measurement of lengths, diameters and thicknesses.

The measure of all things worldwide.

Subject to technical alterations. | Status: 04/2019